



# Product Bulletin

## GULFPRIDE<sup>®</sup> III H ATF

**Gulfpride<sup>®</sup> III H Automatic Transmission Fluid (ATF)** is a multipurpose ATF formulated with premium base stocks and advanced additive technology. It is designed for use in electronic and hydraulic controlled transmissions and can also be used in certain other applications such as power steering units, rotary screw compressors, & some hydraulic fluid applications.

### FEATURES AND BENEFITS:

**Gulfpride<sup>®</sup> III H Automatic Transmission Fluid (ATF)** is a true multipurpose transmission fluid that provides the following benefits:

- Excellent wear protection
- Good anti-foam properties
- Red color for easy identification
- Outstanding oxidation resistance
- Protection against rust and corrosion
- Superior low temperature performance providing good cold-start shifting
- Superior frictional characteristics for smooth shifting

### APPLICATIONS:

**Gulfpride<sup>®</sup> III H Automatic Transmission Fluid (ATF)** is recommended for pre-2006 model General Motors automatic transmissions where a now obsolete Dexron<sup>®</sup> III fluid is specified and post-1981 and pre-2007 Ford automatic transmissions where a now obsolete Mercon<sup>®</sup> fluid is specified. Not for use in applications calling for Dexron<sup>®</sup> VI or Mercon<sup>®</sup> V fluids or in select transmission applications requiring specialized fluids. It is suitable for use where Allison C-4 and Caterpillar TO-2 fluids are required. Additionally, this product is suitable for use in the following applications:

- In powershift transmissions, torque converters and hydrostatic transmissions
- In some hydraulic and compressor systems where excellent low-temperature fluidity and anti-wear properties are required.

Always consult the equipment owner's manual for proper fluid selection.



**AVAILABILITY:**

**Gulfpride® III H Automatic Transmission Fluid (ATF)** is available throughout Gulf's marketing area. Your Gulf representative or Gulf jobber can provide specific information. Need additional information? Call Gulf @ 1-800-566-GULF (4853).

**Gulfpride® III H Automatic Transmission Fluid (ATF) - Typical Properties**

Product Code		332022
	<b>Test Method</b>	
API Gravity	ASTM D-1298	33.6
Specific Gravity	ASTM D-4052	0.8571
Viscosity, cSt @ 40°C	ASTM D-445	37.1
Viscosity, cSt @ 100°C	ASTM D-445	7.5
Viscosity, SUS @ 100°F	ASTM D-2161	183
Viscosity, SUS @ 210°F	ASTM D-2161	52.0
Viscosity Index (min)	ASTM D-2270	170
Brookfield Viscosity, cP @ -40°C	ASTM D-2983	17,500
Brookfield Viscosity, cP @ -20°C	ASTM D-2983	1,300
Pour Point, °F (°C) (max)	ASTM D-5949	-43.6 (-42)
Color	ASTM D-1500	Red