



Product Bulletin

GULF NO RUST C

Gulf No Rust C is a solvent-cutback petroleum compound designed for both ferrous and non-ferrous metal coatings for storage. It forms a continuous protective coating upon evaporation of the solvent. See reverse side for recommended application temperatures.

FEATURES AND BENEFITS:

Gulf No Rust C has unique water displacing characteristics. Additionally, it forms a thin film (less than 1 mm) of protection, providing superior metal surface protection. It provides a coating that will not crack or peel when exposed to a wide range of ambient temperatures.

APPLICATIONS:

Gulf No Rust C is recommended for steel surfaces in a variety of applications including machinery, tools, automotive components, marine hardware, construction equipment and any bare metal surface requiring a protective coating for storage. It is applied by dipping, spraying or brushing at normal room temperatures. It is removed by petroleum solvents or conventional degreasing methods. Safety precautions should be observed in handling these products due to the solvent content.

AVAILABILITY:

Gulf No Rust C is available throughout Gulf's marketing area. Your Gulf representative or Gulf jobber can provide specific information. Need additional information? Call Gulf @ 1-800-566-GULF (4853).



AMERICAN REFINING GROUP, INC.

Master Distributor of Gulf Lubricants • 77 North Kendall Avenue • Bradford, Pennsylvania • 16701
Phone: 814.368.1200 • Fax 814.368.1219 • www.gulflubricants.net • ISO 9001:2008

Gulf No Rust C - Typical Properties

Product Code		335381
Gravity, °API	ASTM D-1298	38.5
Viscosity, SUS @104°F	ASTM D-2161	42
Pour Point, °F (°C)	ASTM D-97	-65 (-54)
Flash Point, TCC, °F (°C)	ASTM D-56	145 (62)
TAN	ASTM D-974	0.31
Sulfur, Total %	IR Spectroscopy	0.62
Salt Water Immersion Test	MIL-L-21260	Pass
Humidity Cabinet Test, Hours		
Polished Panels	ASTM D-1748	720
Sandblasted Panels		720

Summary Application Guide

	No Rust C
Use	Indoor/Outdoor
Coverage, ¹ ft. ² / gal.	4,500
Film Thickness, mm	1
Application Method	Dip
Application Temperature, °F (°C)	40-90 (4-32)
Normal Protection Term, Months	
Indoor	10-12
Outdoor	-
Sheltered	3-4
Unsheltered	-

¹ Multiply by .025 to convert to square meters / liter.