



# Product Bulletin

## Gulfspin 10

**Gulfspin 10** is a high quality spindle oil that eliminates spindle sticking, is non corrosive to metals, protects against oxidation and lowers power requirements.

### FEATURES AND BENEFITS:

**Gulfspin 10** provides excellent resistance to foaming and good air-releasing characteristics. Additionally, it offers the following benefits:

- Excellent rust and corrosion protection
- Minimization of sludge and varnish formations
- High VI with excellent thermal stability
- Good metal wetting ability
- Non staining characteristics

### APPLICATIONS:

**Gulfspin 10** is the right choice for high speed, lightly loaded bearing lubrication found in textile spinning applications and automated machine tools. It can also be used where a low viscosity (ISO VG 10) Rust and Oxidation inhibited hydraulic fluid is required.

### AVAILABILITY:

**Gulfspin 10** is available throughout Gulf's marketing area. Your Gulf representative or Gulf jobber can provide specific information. Need additional information? Call Gulf @ 1-800-566-GULF (4853).

### Gulfspin 10 – R&O Hydraulic Oil Typical Properties

| ISO Viscosity Grade        |                    | 10         |
|----------------------------|--------------------|------------|
| Product Code               | <b>Test Method</b> | 335501     |
| Gravity, API               | ASTM D-1298A       | 36.8       |
| Density, lbs/gal (g/L)     | Calculated         | 7.00 (840) |
| Viscosity, cSt @ 40°C      | ASTM D-445         | 10.0       |
| Viscosity, cSt @ 100°C     | ASTM D-445         | 2.65       |
| Viscosity Index            | ASTM D-2270        | 98.0       |
| Color                      | ASTM D-1500        | L 0.5      |
| Pour Point, °F (°C) (max)  | ASTM D-5949        | -54 (-48)  |
| Flash Point, °F (°C) (min) | ASTM D-92          | 340 (171)  |
| KF Moisture, ppm (max)     | ASTM D-6304        | 200        |

