



Product Bulletin

GULF HIGH TACK BAR & CHAIN OIL

Gulf High Tack Bar & Chain Oil has been formulated as a multi-grade to supercede both of Gulf's previous mono-grades. This product is a true all-season bar and chain lubricant.

FEATURES AND BENEFITS:

Gulf High Tack Bar & Chain Oil has been fortified with extra tackifier to reduce dripping and sling off. Foam inhibitors minimize product foaming, and increased anti-wear agents and detergents insure longer bar, chain, and sprocket life. In addition, this product has exceptional cold temperature characteristics exhibited by a pour point of -25°F.

APPLICATIONS:

Gulf High Tack Bar & Chain Oil helps consolidate inventories and provide better lubricating performance for link chains (mechanical or automatic) in all climates. It is the right choice for all makes of chain saws, motorcycles, and farm equipment, as well as industrial use and link chains where applications require a high-quality bar and chain oil.

AVAILABILITY:

Gulf High Tack Bar & Chain Oil is available throughout Gulf's marketing area. Your Gulf representative or Gulf jobber can provide specific information. Need additional information? Call Gulf @ 1-800-566-GULF (4853).

Gulf High Tack Bar & Chain Oil – Typical Properties

SAE Grade		20W-30
Product Code	Test Method	335704
Viscosity, cSt @ 40°C	ASTM D-445	90
Viscosity, cSt @ 100°C	ASTM D-445	11.5
Viscosity, SUS @ 100°F	ASTM D-2161	418
Viscosity, SUS @ 210°F	ASTM D-2161	65
Pour Point, °F (°C) (max)	ASTM-97	-25 (-30)
Flash Point, COC, °F (°C)	ASTM-92	385 (196)
QC Method #35 / Presence of Tackifier		Pass (Tacky/Stringy)

