



# Product Bulletin

## GULF PREMIUM HEAVY DUTY ELC 50/50 PREDILUTED ANTIFREEZE

**Gulf Premium Heavy Duty ELC 50/50 Prediluted Antifreeze** is made from industrial and antifreeze grade **virgin ethylene glycol** and industry leading additive components. **Gulf Premium Heavy Duty ELC 50/50 Prediluted Antifreeze** is manufactured to contain no phosphates and low silicates. **Gulf Premium Heavy Duty ELC 50/50 Prediluted Antifreeze** is also available pre-diluted 50/50 with de-ionized filtered water making it easier to assure proper coolant mixture for top-off and cooling system fill.

PROPERTIES	METHOD	CONCENTRATE	50/50
Specific Gravity @ 60/60 °F.	ASTM D 1122	1.120	1.065
Boiling Point	ASTM D 1120	327° F.	225° F.
Foam Test	ASTM D 1881	45 ml/ 2.7 seconds	45 ml/ 2.7 seconds
pH, 50% Volume Solution	ASTM D 1287	10.4	10.4
Reserve Alkalinity	ASTM D 1121	6.8 ml	3.5 ml
Water, % volume	ASTM D 1123	2.8%	51.4%
Glycol, % volume	ASTM E 202	95.0% Minimum	47.5% Minimum
Nitrite Content		1400 ppm	700 ppm
Additional Inhibitors **This includes Nitrate and Borate Content		1400 ppm**	700 ppm
<b>Product Number:</b>			<b>841119</b>

When used as directed, **Gulf Premium Heavy Duty ELC 50/50 Prediluted Antifreeze** meets:\*

<u>AUTOMOTIVE</u>	<u>HEAVY-DUTY</u>
ASTM D-3306, ASTM D-4340	ASTM D-4985
GM 6038M	Cummins 90T8-4
CSMA	Detroit Diesel 7SE298
Chrysler MS 7170	Freightliner 48-22880
Ford ESE-M97B44-A	GM 1899M (Non-Aluminum)
GM 1825M (Aluminum)	John Deere H24B1, H24C1, H5
GSA A-A- 52624, GSA A-A-0870	Mack TO 14, GS 17004
SAE J1034, J814	RP-302 A, B,C
VW TL 774 (G11)	SAE J 1941
Porsche TL774C	Volvo/GM Heavy Truck Corporation
American Motors AM-4085	Ford New Holland WSN-M97D18D
MIL-O-A-5480	J.I. Case JIC-501, MS1710
	Ford ESE M97B18-C
	Toyota TSK26016
	Navistar B1, Type 1

\*Always consult owner's manual to determine the specific OEM recommended fluid, maintenance, changeover intervals and Extender/SCA treat rate for your vehicle.



Master Distributor of Gulf Lubricants • 77 North Kendall Avenue • Bradford, Pennsylvania • 16701  
Phone: 814.368.1200 • Fax 814.368.1219 • [www.gulflubricants.net](http://www.gulflubricants.net) • ISO 9001:2008